

Bio-adhesive butyl sealant tape, thickness 2x60

- cod. 11111003 - cod. 11111003BOX



DIMENSIONS

CODE	WIDTH [mm]	LENGTH [m]	THICKNESS [mm]
11111003	60	10	2
11111003BOX	60	10	2

DESCRIPTION

Double-sided adhesive tape consisting of a highly adhesive butyl compound reinforced with polyester mesh. The butyl tape has been studied and developed as a connection and connecting element between sheets or solar panels and for fixing and joining them.

The tape is used for fastening and sealing photovoltaic panels.

Use within 12 months.

For correct storage, it is recommended to keep the product in its original unopened packaging and to store it in a dry and well-ventilated place.

Storage at a temperature above 50°C may cause detachment difficulties during installation.

Frost-resistant.

TECHNICAL SPECIFICATIONS

SPECIFICATIONS	TEST	VALUES
Thickness		2 mm
Compound Colour		Black
Tensile properties	EN 12311-1	Long. 115 N/50 mm Transv. 140 N/50 mm
Elongation at break	EN 12311-2	Long. 15% Transv. 15%
Solid		100%
Peel adhesion 180°	ASTM D 1000	31 N/cm
Probe Track	ASTM D 2979	9 N
Temperature of application		+5°C / +40°C
Operating temperature		-40°C/+130°C
Classification for transport		Not applicable
Fire reaction class	EN 13501-1	E

PRELIMINARY CHECKS

The surfaces on which the tapes are applied must be dry, clean and free of impurities. In the presence of porous supports, it is advisable to stabilise the surface.

INSTALLATION PROCEDURES

1. Apply the tape.
2. Press hard.
3. Remove the silicone film.
4. Lay the element to be fastened or joined.

ITEMS

CODE	DESCRIPTION
11111003	BIADHESIVE BUTYL SEALER TAPE
11111003BOX	BIADHESIVE BUTYL SEALER TAPE - BOX 3 pcs

All rights relating to this publication are the exclusive property of Tecnosystemi SpA. Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.