

# Sheath for gas pipes in spiral PVC for wall chase

- cod. 25000600 - cod. 25000610 - cod. 25000620  
- cod. 25000650 - cod. 25000660



## TECHNICAL SPECIFICATIONS:

- Anti-crush plastic-coated spiral PVC
- Smooth interior
- Yellow colour
- Self-extinguishing UL V0
- Operating temperature: -15°C to +60°C
- Built according to UNI CIG 7129 standards for the protection and insulation of pipes in the transport of fuel gas
- Reel length 25 m

## ITEMS

CODE	DESCRIPTION
25000600	SPIRALED PVC CONDUIT FOR GAS PIPING IN BURIED INSTALLATIONS Ø20
25000610	SPIRALED PVC CONDUIT FOR GAS PIPING IN BURIED INSTALLATIONS Ø25
25000620	SPIRALED PVC CONDUIT FOR GAS PIPING IN BURIED INSTALLATIONS Ø30
25000650	SPIRALED PVC CONDUIT FOR GAS PIPING IN BURIED INSTALLATIONS Ø50
25000660	SPIRALED PVC CONDUIT FOR GAS PIPING IN BURIED INSTALLATIONS Ø60

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.  
Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.