


1 kg/h low pressure regulator with adjustable calibration for LPG

- cod. 21000010



TECHNICAL SPECIFICATIONS:

- Horizontal coupling
- Capacity 1 kg/h
- Calibration 20 - 60 mbar
- Export model
- Suitable for use with butane

Body and lid in Zama (ZL5) according to EN 1774 and protected with galvanisation

- Membrane and rubber pad: NBR according to Standard EN 549
- Nut in brass CW 617 N Standard EN 12165 or in steel AVP

OPERATING SPECIFICATIONS

- Guaranteed load capacity (Mg): 1 kg/h
- Feed pressure: $P_{dmax} +0.2 \div 7.5$ bar (Butane)
- Nominal output pressure: (Pd): Variable from 20 to 60 mba
- Operating temperature Min. -20 °C ÷ Max. $+60$ °C

INLET CONNECTIONS (DEPENDING ON COUNTRY OF DESTINATION)

- Threaded: from G.1 to G.21

OUTLET CONNECTIONS (DEPENDING ON COUNTRY OF

DESTINATION)

- Threaded: from H.1 to H.9
- Non-threaded: from H.50 to H.54

TECHNICAL DATA

CODE	COUPLER INLET	COUPLER OUTLET
21000010	ITALY NUT W 20 x 14 LH	HOSE FITTING

ITEMS

CODE	DESCRIPTION
21000010	ADJUSTABLE SETTING LOW-PRESSURE REGULATOR 1KG/H

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.
Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.