

product details

Pack of 3 flexible hoses with 45° long ball valves for gas TR422ABCD (R22) - R407C - R410A - R32

COD. 11132026 - 11132027 - 11132119



**TECHNICAL SPECIFICATIONS:**

- Max operating pressure: 500 psi/45 bar (for gas TR422ABCD (R22) - R407C)
- Max operating pressure: 800 psi / 55 bar (for gas R410A - R32)
- Max length 1500 or 3000 mm
- 1/4" SAE x 1/4 SAE 45° yellow/red/blue pipe (for gas TR422ABCD (R22) - R407C)
- 1/4" SAE x 5/16" SAE 45° red/blue pipe (for gas R410A/R32 ) 1/4" SAE x 1/4 SAE 45° yellow (for gas R410A/R32)

CODE	LENGTH [mm]
11132026	1500
11132027	1500
11132119	3000

CODE	DESCRIPTION
11132026	FLEXIBLE HOSES WITH SHUT OFF VALVE FOR GAS R407C/R22(mm.1500)
11132027	FLEXIBLE HOSES WITH SHUT OFF VALVE FOR GAS R410A (mm.1500)
11132119	FLEXIBLE HOSES WITH SHUT OFF VALVE FOR GAS R410A(mm.3000)