

Gas flexible hose for kitchen connection covered in transparent sheath M / F

- cod. 25000060 - cod. 25000070 - cod. 25000080
- cod. 25000090 - cod. 25000100 - cod. 25000110



TECHNICAL SPECIFICATIONS:

- Twist in stainless steel AISI 304 EN 10088 - 1DIN 1.4301
- AISI 316L EN 10088 - 1 DIN 1.4404 stainless steel pipe
- 1/2" couplings stainless steel AISI 303 EN 10088 - 1 DIN 1.4301
- Outer yellow PVC coating - transparent self-extinguishing
- Max pressure 0.5 bar
- Max temperature +100 °C
- Available in 500 - 750 - 1000 - 1250 - 2000 mm
- Flexible pipe with gaskets and sealing caps

ITEMS

CODE	DESCRIPTION
25000060	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 500MM
25000070	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 750MM
25000080	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 1000MM
25000090	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 1250MM
25000100	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 1500MM
25000110	HOSE COVERED IN CONDUIT M/F 1/2", LENGHT 2000MM

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.