ATLANTIS AA



wall-mounted programmable chrono-thermostat for room with touch screen, battery-run

- cod. 11181423



DESCRIPTION

The programmable thermostat is fastened to the wall very quickly.

The programmable thermostat can be detached from the seat at any time with a slight external pressure by means of a coupling template supplied.

The presence of the touch buttons and of the 4.5" LCD display make the programmable thermostat easy and intuitive even for the less experienced user.

Power supply and data transmission by wiring.

Wall-mounting using the practical template supplied.

Built-in antifreeze function.

Operation with step-by-step relay.

TECHNICAL SPECIFICATIONS:

- Wall mounted using template, screw and fixing plugs supplied
- Power supply battery 2 x 1.5 V type AA (LR6) supplied
- Battery life 18 months
- 4.5" LCD display
- Touch keypad
- Timed or manual features
- Timed thermostat lock
- Temperature scale °C/°F
- RH value as a percentage %
- AT and Set Point value
- Clock (AM PM / 24h)
- Temperature set from +10°C to +35°C
- Working temperature +5°C to +50°C
- 4 Daily time slots
- Daily and weekly feature



DATASHEET

- Latching relay (no static consumption) for boiler piloting
- Antifreeze feature
- Lumix white colour

CONTACT CAPACITY:

- 3A at 230 V AC on resistive load 2A at 230 V AC on inductive load
- 3A at 30 V DC on resistive load 2A at 30 V DC on inductive load

ITEMS

CODE	DESCRIPTION
11181423	TOUCH SCREEN, PROGRAMMABLE, WALL CHRONOTERMOSTAT W/BATTERIES "ATLANTIS AA"

All rights relating to this publication are the exclusive property of Tecnosystemi SpA. Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.