

# 30 m coiled PVC condensate drain pipe for duct installation

- cod. SCD300098 - cod. 111263268 - cod. SCD300099  
- cod. SCC300006 - cod. 111263274



## TECHNICAL SPECIFICATIONS:

- Plastic-coated rigid PVC-based material
- Flexibility: passes the test of no. 3000 flexions at 180° + 5°C and + 60°C.
- Bending radius: two times the diameter
- Crush resistance: class 2 greater than 220 Newton over 5 cm at + 23 ± 2°C
- Impact resistance: class 3 2 kg from 10 cm at -5°C.
- Minimum temperature: class 1 + 5°C -- Maximum temperature class 1 + 60°C.
- Electrical insulation resistance: greater than 100 megohms for 500 V operation for 1 min
- Fire resistance: passes "Glow wire test" at 850°C according to standard IEC EN 60695-2-11

## DIMENSIONS

| CODE      | Ø [mm] | ROLL [m] |
|-----------|--------|----------|
| SCD300098 | 16     | 30       |
| 111263268 | 18     | 30       |
| SCD300099 | 20     | 30       |
| SCC300006 | 25     | 30       |
| 111263274 | 32     | 30       |

## ITEMS

| CODE      | DESCRIPTION                                                                                      |
|-----------|--------------------------------------------------------------------------------------------------|
| SCD300098 | CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 16 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT) |
| 111263268 | CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 18 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT) |
| SCD300099 | CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 20 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT) |
| SCC300006 | CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 25 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT) |
| 111263274 | CONDENSATE DRAIN HELIX HOSE SINGLE LAYER Ø 32 FOR INSTALLATION IN A CHASE OR IN TRUNKING (30 MT) |

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.  
Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.

