

45° Curve F / F in copper

- cod. 11110598 - cod. 11110630 - cod. 11110631
- cod. 11110632 - cod. 11110633 - cod. 11110634
- cod. 11110635 - cod. 11110636 - cod. 11110637



TECHNICAL SPECIFICATIONS:

- Measurements in inches
- Polished interior
- Female/ female coupling
- Pressione massima di esercizio 43 bar
- Temperatura media di esercizio -40°C / +120°C
- Campo di applicazione: impianti di condizionamento e refrigerazione

TECHNICAL DATA

CODE	Ø [inch]	Ø [mm]	SPESSORE RAME [mm]	PRESSIONE MAX DI ESERCIZIO [bar]
11110598	1/2"	12,7	1	43
11110630	5/8"	15,80	1	43
11110631	3/4"	19,05	1	43
11110632	7/8"	22,22	1	43
11110633	1"	25,40	1	43
11110634	1" 1/8	28,57	1	43
11110635	1" 1/4	31,75	1	43
11110636	1" 3/8	34,92	1,2	43
11110637	1" 5/8	41,27	1,2	43

ARTICOLI

CODE	DESCRIPTION
11110598	COPPER ELBOW 45° F-F 1/2"
11110630	COPPER ELBOW 45° F-F 5/8"
11110631	COPPER ELBOW 45° F-F 3/4"
11110632	COPPER ELBOW 45° F-F 7/8"
11110633	COPPER ELBOW 45° F-F 1"
11110634	COPPER ELBOW 45° F-F 1" 1/8"
11110635	COPPER ELBOW 45° F-F 1" 1/4"
11110636	COPPER ELBOW 45° F-F 1" 3/8"
11110637	COPPER ELBOW 45° F-F 1" 5/8"

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.
Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.

