

F/F copper sleeve

- cod. 11110596 - cod. 11110600 - cod. 11110601
- cod. 11110602 - cod. 11110603 - cod. 11110604
- cod. 11110622 - cod. 11110605 - cod. 11110618



TECHNICAL SPECIFICATIONS:

- Measurements in inches
- Polished interior
- Female/ female coupling
- Pressione massima di esercizio 43 bar
- Temperatura media di esercizio -40°C / +120°C
- Campo di applicazione: impianti di condizionamento e refrigerazione

TECHNICAL DATA

CODE	Ø [inch]	Ø [mm]	SPESSORE RAME [mm]	PRESSIONE DI ESERCIZIO [bar]
11110596	1/2"	12,7	1	43
11110600	5/8"	15,80	1	43
11110601	3/4"	19,05	1	43
11110602	7/8"	22,22	1	43
11110603	1"	25,40	1	43
11110604	1" 1/8	28,57	1	43
11110622	1" 1/4	31,75	1	43
11110605	1" 3/8	34,92	1,2	43
11110618	1" 5/8	41,27	1,2	43

ARTICOLI

CODE	DESCRIPTION
11110596	COPPER SLEEVE M-M 1/2"
11110600	COPPER SLEEVE 5/8"
11110601	COPPER SLEEVE 3/4"
11110602	COPPER SLEEVE 7/8"
11110603	COPPER SLEEVE 1"
11110604	COPPER SLEEVE 1" 1/8"
11110622	COPPER SLEEVE 1" 1/4
11110605	COPPER SLEEVE 1" 3/8"
11110618	COPPER SLEEVE 1" 5/8"

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.
Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.

