

Extensible gas hose for boiler connection coated in yellow polyolefin M / F

25000120 - 25000130 - 25000140
 25000150 - 25000160 - 25000170
 25000180 - 25000190 - 25000200
 25000210 - 25000220 - 25000230
 25000240 - 25000250 - 25000260
 25000270



TECHNICAL SPECIFICATIONS:

- Max operating temperature +100°C
- AISI 316L stainless steel hose
- Stainless steel AISI 303 thread
- With yellow self-shrinking polyolefin protective sheath
- Inlet pressure max 0.5 bar

ITEMS

CODE	DESCRIPTION
25000120	COVERED EXTENDABLE HOSE Ø12 , L.80-120 MM, F1/2" M1/2"
25000130	COVERED EXTENDABLE HOSE Ø12 , L.120-200 MM, F1/2" M1/2"
25000140	COVERED EXTENDABLE HOSE Ø12 , L.220-400 MM, F1/2" M1/2"
25000150	COVERED EXTENDABLE HOSE Ø12 , L.280-520 MM, F1/2" M1/2"
25000160	COVERED EXTENDABLE HOSE Ø12 , L.80-120 MM, F3/4" M1/2"
25000170	COVERED EXTENDABLE HOSE Ø12 , L.120-200 MM, F3/4" M1/2"
25000180	COVERED EXTENDABLE HOSE Ø12 , L.220-400 MM, F3/4" M1/2"
25000190	COVERED EXTENDABLE HOSE Ø12 , L.280-520 MM, F3/4" M1/2"
25000200	COVERED EXTENDABLE HOSE Ø20 , L.80-120 MM, F3/4" M3/4"
25000210	COVERED EXTENDABLE HOSE Ø20 , L.120-200 MM, F3/4" M3/4"
25000220	COVERED EXTENDABLE HOSE Ø20 , L.220-400 MM, F3/4" M3/4"
25000230	COVERED EXTENDABLE HOSE Ø20 , L.280-520 MM, F3/4" M3/4"
25000240	COVERED EXTENDABLE HOSE Ø25 , L.80-120 MM, F1" M1"
25000250	COVERED EXTENDABLE HOSE Ø25 , L.120-200 MM, F1" M1"
25000260	COVERED EXTENDABLE HOSE Ø25 , L.220-400 MM, F1" M1"
25000270	COVERED EXTENDABLE HOSE Ø25 , L.280-520 MM, F1" M1"