

DATASHEET

rev. 00 - 28/11/2022



Gas flexible hose for kitchen connection covered in transparent sheath F / F

25000000 - 25000010 - 25000020
25000030 - 25000040 - 25000050



TECHNICAL SPECIFICATIONS:

- Twist in stainless steel AISI 304 EN 10088 - 1din 1.4301
- AISI 316L EN 10088 - 1 DIN 1.4404 stainless steel pipe
- 1/2" couplings stainless steel AISI 303 EN 10088 - 1 DIN 1.4301
- Outer yellow PVC coating - transparent self-extinguishing
- Max pressure 0.5 bar
- Max temperature +100°C
- Available in 500 - 750 - 1000 - 1250 - 2000 mm
- Flexible pipe with gaskets and sealing caps

ITEMS

CODE	DESCRIPTION
25000000	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 500MM
25000010	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 750MM
25000020	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 1000MM
25000030	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 1250MM
25000040	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 1500MM
25000050	HOSE COVERED IN CONDUIT F/F 1/2", LENGHT 2000MM