

PA-PLUS

digital current clamp

11131113



TECHNICAL SPECIFICATIONS:

- Backlit LCD display, max display value 4000
- Maximum measurable current 400 A
- Maximum conductor cross-section 30 mm (11.8")
- Range: Aca/Ua, Dca/Ua, ACV, DCV, Ohm, continuity, capacity and temperature
- Continuity buzzer (<40 ohm)
- Alternating current 0.1- 4000 Ua/0.01 A - 400 A ± (2.0% +10)
- Direct current 0.1- 4000 Ua ± (1.0% +2)
- Alternating voltage 1 mv-600 V ± (1.0% +3)
- Continuous voltage 1m v-600 V ± (0.8% +2)
- Temperature (K) -50° C - 1200° C e 158° F - 1999° F
- Low battery indication
- Auto shut-down (30 minutes)
- R-H range block
- Select: selection button for Aca/Ua, Dcua, Acv/Dcv and Ohm/Continuity composite functions.
- Overload display
- Automatic range
- D-h data block
- Weight 280 g
- Power supply battery 2 x 1.5 V type supplied
- Dimensions W 205 x H 39 x D 64 mm

ITEMS

| CODE | DESCRIPTION |
|----------|---------------------------------|
| 11131113 | DIGITAL CURRENT CLAMP "PA PLUS" |