

Delivery / return plenum with made-tomeasure reduced window coupler in aluminate pole for duct systems

11161605F - 11161606F - 11161607F PWD400114




TECHNICAL SPECIFICATIONS:

- Made of high quality 80 μ aluminium foil, embossed and lacquered, insulated with stiff expanded polyisocyanurate (PIR) foam
- Overall thickness 20 mm fire-retardant, highly heat-insulating, waterproof
- Includes fastening flange

DIMENSIONS

- Provide dimensions of delivery outlet (A1 x B1 mm, C 260 mm fixed) of indoor unit
- Provide outer plenum dimensions (A x B mm, C 300 mm fixed)



CODE	MODEL	INTERNAL HEIGHT A [mm]	INTERNAL WIDTH B [mm]	INTERNAL DEPTH c [mm]
11161605F	mod. 1/F	on request up to 300	on request up to 1000	260 FISSA
11161606F	mod. 2/F	on request up to 400	on request up to 1200	260 FISSA
11161607F	mod. 3/F	on request up to 400	on request up to 1500	260 FISSA
PWD400114	mod. 4/F	on request up to 500	on request up to 1700	260 FISSA

ITEMS

CODE	DESCRIPTION		
11161605F	SUPPLY/RETURN PLENUM WITH REDUCED WINDOW COUPLING FOR PAL ALUMINIUM CUSTOMIZED DUCTS MOD.1/F		
11161606F	SUPPLY/RETURN PLENUM WITH REDUCED WINDOW COUPLING FOR PAL ALUMINIUM CUSTOMIZED DUCTS MOD.2/F		
11161607F	SUPPLY/RETURN PLENUM WITH REDUCED WINDOW COUPLING FOR PAL ALUMINIUM CUSTOMIZED DUCTS MOD.3/F		
PWD400114	SUPPLY/RETURN PLENUM WITH REDUCED WINDOW COUPLING FOR PAL ALUMINIUM CUSTOMIZED DUCTS MOD.7/F		