

DATASHEET

rev. 00 - 10/11/2022


Insulated reduction for 3-way insulated shunts

PWC500013 - PWC500014 - PWC500015
PWC500016



TECHNICAL SPECIFICATIONS:

- Made of n PP
- Insulating coating: polyethylene with aluminium coating
- Operating temperature: 0°C to +70°C
- Only in combination with 3-way insulated shunts
- For flexible heating and air conditioning pipes (insulated or not)



DIMENSIONS

CODE	PIPE COUPLER Ø 1 [mm]	SHUNT COUPLER Ø 2 [mm]
PWC500013	150	200
PWC500014	200	250
PWC500015	250	300
PWC500016	300	350

ITEMS

CODE	DESCRIPTION
PWC500013	INSULATED ADAPTER FOR 3-WAY INSUALTED BRANCHES FROM Ø 200 mm TO Ø 150 mm
PWC500014	INSULATED ADAPTER FOR 3-WAY INSUALTED BRANCHES FROM Ø 250 mm TO Ø 200 mm
PWC500015	INSULATED ADAPTER FOR 3-WAY INSUALTED BRANCHES FROM Ø 300 mm TO Ø 250 mm
PWC500016	INSULATED ADAPTER FOR 3-WAY INSUALTED BRANCHES FROM Ø 350 mm TO Ø 300 mm