

DATASHEET

rev. 01 - 10/11/2022

Spray system washing

11132286 - 11132285 - 11132288
TSC600044



DESCRIPTION

Spray liquid solvent for the (manual) internal washing of the systems, particularly suitable for cleaning in case of compressor replacement.

Evaporates very quickly.

It thoroughly removes all oil residues, rust, deposits and moisture inside the system. Totally compatible with rubber and metal components.

TECHNICAL SPECIFICATIONS:

- Appearance: colourless liquid
- Relative density [g/m³]: 0.75- 0.85 kg/l (± 0.04)
- Vapour density > 2
- Hydrosolubility: insoluble
- Delivery power: up to 8~10 m

USES

This liquid solvent is specifically used for flushing the internal piping of car air-conditioning systems and refrigeration systems. The flushing of air conditioning systems is one of the most important tasks in the event of repair or damage to the compressor. Flushing removes impurities and harmful substances from the air conditioning circuit.

It is necessary to carry out repairs in a workmanlike manner and to avoid costly subsequent repairs. This also protects warranty rights to suppliers and ensures customer satisfaction.

However, it is not possible to flush compressors, expansion/orifice valves, dryer filters or accumulators, they will therefore have to be bypassed with adaptors during the flushing cycle.

The valves and filters must be replaced at the end of the cleaning cycle.

WARNINGS

Do not flush compressors, expansion/orifice valves, filter dryers or accumulators.

SAFETY INFORMATION

Read and observe the safety warnings on the container's label. For information regarding handling, transportation, etc., refer to the Safety Data Sheet (SDS) for the product in question.

ITEMS

CODE	DESCRIPTION
11132286	SYSTEM CLEANER SPRAY KIT WITH DISPENSER 750 ml
11132285	SPARE DISPENSER FOR SYSTEM CLEANER SPRAY KIT 750 ml
11132288	SYSTEM CLEANER SPRAY KIT WITH DISPENSER 500 ml
TSC600044	DISPENSER INCLUDING FLEX. HOSE FOR WASHING SPRAY SYSTEM