

DATASHEET

rev. 00 - 7/11/2022



BEV

two-stage vacuum pump with solenoid valve and vacuum gauge for R32 gas

TSC100001 - TSC100002 - TSC100008
TSC100009 - TSC100016 - TSC100017



TECHNICAL SPECIFICATIONS:

- Two-stage pump
- Vacuum rating 0.3 Pa/25 μ
- Built-in non-return valve
- Solenoid valve
- Power supply 230V - 50Hz
- 1/4" SAE - 3/8" SAE pump coupling, depending on the model
- Vacuum gauge \varnothing 80 mm
- Can be used with all types of gas, even with R32

TECHNICAL DATA

MODEL	FLOW RATE [l/min]	DEGREE OF VACUUM	POWER [hp]	FLEXIBLE HOSE COUPLER	OIL TANK CAPACITY [ml]	WEIGHT [kg]
TS42 BEV	42	0.3 Pa/25 μ	1/4	1/4"	180	6,3
TS70 BEV	70	0.3 Pa/25 μ	1/3	1/4"	280	7,3
TS128 BEV	128	0.3 Pa/25 μ	1/2	1/4" - 3/8"	350	11,8
TS170 BEV	170	0.3 Pa/25 μ	3/4	1/4" - 3/8"	500	14
TS100 BEV	100	0.3 Pa/25 μ	1/3	1/4" - 3/8"	360	11
TS226 BEV	226	0.3 Pa/25 μ	1	1/4" - 3/8"	600	15,5

ITEMS

CODE	DESCRIPTION
TSC100001	"TS42 BEV" TWO-STAGE VACUUM PUMP FOR GAS R32
TSC100002	"TS70 BEV" TWO-STAGE VACUUM PUMP FOR GAS R32
TSC100008	"TS42 BEV" TWO-STAGE VACUUM PUMP MODEL FOR R32 GAS
TSC100009	"TS70 BEV" TWO-STAGE VACUUM PUMP FOR R32 GAS
TSC100016	"TS100 BEV" TWO-STAGE VACUUM PUMP FOR R32 GAS
TSC100017	"TS226 BEV" TWO-STAGE VACUUM PUMP FOR R32 GAS