

GREY LINE

single insulated copper pipe 50 m

SCD600010 - SCD600011 - SCD600012
SCD600013 - SCD600014



TECHNICAL SPECIFICATIONS:

- Cu-DHP copper pipe according to EN 12735-1
- Closed-cell polyethylene foam sheath
- Strong tear-resistant grey-coloured, corrugated and pyramidal outer film
- Insulation thickness from 6 to 10 mm
- Copper thickness from 0.8 to 1 mm

TECHNICAL DATA

CODE	Ø	[mm]	COPPER THICKNESS [mm]	SHEATH THICKNESS [mm]
SCD600010	CU 1/4"	6,35	0,8	6
SCD600011	CU 3/8"	9,52	0,8	6
SCD600012	CU 1/2"	12,7	0,8	6
SCD600013	CU 5/8"	15,88	1	10
SCD600014	CU 3/4"	19,05	1	10

TECHNICAL SPECIFICATIONS OF THE SHEATH

SPECIFICATIONS	TECHNICAL DATA
TEMPERATURE OF USE	-45°C + 100°C
SPECIFIC WEIGHT	35 kg/m ²
THERMAL CONDUCTIVITY COEFFICIENT DIN 52613	0.0040 W/mK
WATER VAPOUR PERMEABILITY DIN 52615	N6200
SHEATH THICKNESS	6 mm: 1/4" - 3/8" - 1/2"; 10 mm: 5/8" - 3/4"
REACTION TO FIRE CLASS (13501)	Cl-s1,d0

ITEMS

CODE	DESCRIPTION
SCD600010	"GREY LINE" - 1/4" INSULATED COPPER PIPE- COPPER THICKNESS 0,8 mm, 50 meter
SCD600011	"GREY LINE" - 3/8" INSULATED COPPER PIPE- COPPER THICKNESS 0,8 mm, 50 meter
SCD600012	"GREY LINE" - 1/2" INSULATED COPPER PIPE- COPPER THICKNESS 0,8 mm, 50 meter
SCD600013	"GREY LINE" - 5/8" INSULATED COPPER PIPE- COPPER THICKNESS 1,0 mm, 50 meter
SCD600014	"GREY LINE" - 3/4" INSULATED COPPER PIPE- COPPER THICKNESS 1,0 mm, 25 meter