

DATASHEET

rev. 00 - 28/11/2022

insulating dielectric threaded joint M / F for
water and gas utilities PN10

25000800 - 25000810 - 25000820

25000830 - 25000840 - 25000850



TECHNICAL SPECIFICATIONS:

- In accordance with UNI 10284
- Max pressure 10 bar
- Test pressure 16 bar
- Max temperature 70°C
- M/F couplings

ITEMS

CODE	DESCRIPTION
25000800	THREADED DIELECTRIC INSULATING JOINT M-F FOR WATER AND GAS UTILITIES PN10 1/2"
25000810	THREADED DIELECTRIC INSULATING JOINT M-F FOR WATER AND GAS UTILITIES PN10 3/4"
25000820	THREADED DIELECTRIC INSULATING JOINT M-F FOR WATER AND GAS UTILITIES PN10 1"
25000830	THREADED DIELECTRIC INSULATING JOINT M-F FOR WATER AND GAS UTILITIES PN10 1"1/4"
25000840	THREADED DIELECTRIC INSULATING JOINT M-F FOR WATER AND GAS UTILITIES PN10 1"1/2"
25000850	THREADED DIELECTRIC INSULATING JOINT M-F FOR WATER AND GAS UTILITIES PN10 2"