

# DATASHEET

rev. 01 - 28/11/2022



1 kg/h low pressure regulator with adjustable calibration for LPG

21000010



## TECHNICAL SPECIFICATIONS:

- Horizontal coupling
- Capacity 1 kg/h
- Calibration 20 - 60 mbar
- Export model
- Suitable for use with butane

Body and lid in Zama (ZL5) according to EN 1774 and protected with galvanisation

- Membrane and rubber pad: NBR according to Standard EN 549
- Nut in brass CW 617 N Standard EN 12165 or in steel AVP

## OPERATING SPECIFICATIONS

- Guaranteed load capacity (Mg): 1 kg/h
- Feed pressure: P<sub>dmax</sub> +0.2÷7.5 bar (Butane)
- Nominal output pressure: (Pd): Variable from 20 to 60 mba
- Operating temperature Min. -20 °C + Max. +60°C

## INLET CONNECTIONS (DEPENDING ON COUNTRY OF DESTINATION)

- Threaded: from G.1 to G.21

## OUTLET CONNECTIONS (DEPENDING ON COUNTRY OF DESTINATION)

- Threaded: from H.1 to H.9
- Non-threaded: from H.50 to H.54

## TECHNICAL DATA

CODE	COUPLER INLET	COUPLER OUTLET
21000010	ITALY NUT W 20 x 14 LH	HOSE FITTING

## ITEMS

CODE	DESCRIPTION
21000010	ADJUSTABLE SETTING LOW-PRESSURE REGULATOR 1KG/H