

FST225-180R

adjustable support for fixing on roofs with roof tiles and tiles


- cod. 11110764 - cod. 11110764BOX



TECHNICAL SPECIFICATIONS:

- Material: AISI 304 stainless steel
- Flexural modulus of elasticity: 196000 N/mm²
- Tensile breaking load: 515 N/mm²
- Hook dimensions: 30mm x 5mm thickness
- 3 holes Ø 9 prepared for plate fixing

TECHNICAL DRAWING:




FULL SIZED:

CODE	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]
11110764	175 - 215	95 - 135	65	115	30	110	30
11110764BOX	175 - 215	95 - 135	65	115	30	110	30

APPLICATION:

Fixing of photovoltaic systems on roofing tiles supported by strips of varying thickness.



ITEMS

CODE	DESCRIPTION
11110764	INOX AISI 304 ADJUSTABLE SUPPORT FOR FIXING INTO ROOFS MOD. FST225-180R
11110764BOX	INOX AISI 304 ADJUSTABLE SUPPORT FOR FIXING INTO ROOFS MOD. FST225-180R - BOX 10 pcs

All rights relating to this publication are the exclusive property of Tecnosystemi SpA.
Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.

