SMART SIRIO

 ϵ

programmable thermostat for room with summer/winter switching

- cod. SGC200001



DESCRIPTION

The SMART SIRIO programmable thermostat has easy settings as it is simple and intuitive in daily use by the end user. It allows use of the external probe and management of the boiler, a zone unit or the switching on and off of a fan coil through the 230 V - 50 Hz 16A / 3600 W output contact.

The SMART SIRIO programmable thermostat also has a sub-menu thanks to which it is possible to enable a series of options capable of transforming the programmable thermostat into a multifunctional device, for example:

- Provide a reminder to replace UV lamp (if present)
- Set a timer to replace filters
- Manage the presence of an external probe, if any

The SMART SIRIO programmable thermostat can be combined with a SIRIO 2.0 Point damper or a SIRIO 2.0 Pack Point system.

TECHNICAL SPECIFICATIONS:

- Dual power supply with 2 x 1.5V AA batteries or 24 V AC
- Contact rating 2A
- Setpoint range 5 35°C
- Accuracy ± 0.5°C
- Scale °C/°F
- Summer / winter mode
- Fan activation option
- Programmable at 7 days or 5+1+1 up to 4 time slots
- Option to set a UV lamp change reminder at 400 days or a filter change (config. 1 to 12 months)
- 4"display, blue backlight
- Keypad for function selection
- Rotary parameter adjustment selector
- Quick fastening to wall by means of template
- Dimensions 140 x 90 x 32 mm



DATASHEET

ITEMS

CODE	DESCRIPTION
SGC200001	"SMART SIRIO" ROOM CHRONO-THERMOSTAT WITH SUMMER/WINTER SWITCHING

Tecnosystemi SpA reserves the right to make changes at any time and without notice, for technical or commercial needs.

SHOWGAS by In Tecnosyst